

TVAR PRVKU	Objednáací číslo	Tloušťka [mm]	C [mm]	D [mm]	E [mm]	Rozvinutá šířka [mm]	Hmotnost [kg/m]	Pro typ trap. pl.	Z = provedení pozink. X = lze dodat i v jiné tloušťce
	OKAPNICE STĚNOVÁ							X	
	4-050.1	0,63	119	30	40	208	1,05		
	4-050.2	0,63	104	45	55	208	1,05		
	4-150.1	0,75	119	30	40	208	1,25		
	4-150.2	0,75	104	45	55	208	1,25		
	VNĚJŠÍ NÁROŽÍ (rovnoramenné)							X	
	4-051.1	0,63			110	250	1,26		
	4-051.2	0,63			190	416	2,10		
	4-151.1	0,75			110	250	1,50		
	4-151.2	0,75			190	416	2,50		
	VNĚJŠÍ NÁROŽÍ (nerovnoramenné)							X	
	4-052.1	0,63				312	1,57		
	4-152.1	0,75				312	1,87		
	VNITŘNÍ NÁROŽÍ (rovnoramenné)							X	
	4-053.1	0,63				208	1,05		
	4-153.1	0,75				208	1,25		
	PŘIPOJOVACÍ PROFIL (trapezového plechu)							X	
	4-054.1	0,63	35	27	221	312	1,57	TR 30/220	
	4-054.2	0,63	35	34	220	312	1,57	TR 35/207	
	4-054.3	0,63	35	40	220	312	1,57	TR 40/183	
	4-054.4	0,63	25	18	247	312	1,57	TR 20/137	
	4-154.1	0,75	35	27	221	312	1,87	TR 30/220	
	4-154.2	0,75	35	34	220	312	1,87	TR 35/207	
	4-154.3	0,75	35	40	220	312	1,87	TR 40/183	
	4-154.4	0,75	25	18	247	312	1,87	TR 20/137	
		UKONČENÍ STĚNY							X
4-055.1		0,63		156		416	2,10		
4-055.2		0,63		365		625	3,15		
4-155.1		0,75		156		416	2,50		
4-155.2		0,75		365		625	3,75		
	UKONČENÍ STĚNY (pro pultovou střechu)							X	
	4-056.1	0,63		156		416	2,10		
	4-156.1	0,75		156		416	2,50		
	Nutno zadat úhel α .								