

| TVAR PRVKU | Objednáací číslo | Tloušťka [mm] | C [mm] | D [mm] | E [mm] | Rozvinutá šířka [mm] | Hmotnost [kg/m] | Z = provedení pozink. X = lze dodat i v jiné tloušťce |
|---|--|---------------|--------|--------|--------|----------------------|-----------------|--|
| | Z - PROFIL (distanční) | | | | | | | Z X |
| | 1-401.1 | 1,25 | 46 | 60 | | 156 | 1,56 | |
| | 1-401.2 | 1,25 | 58 | 70 | | 178 | 1,78 | |
| | 1-401.3 | 1,25 | 48 | 80 | | 178 | 1,78 | |
| | 1-501.4 | 1,50 | 68 | 90 | | 208 | 2,50 | |
| | 1-501.5 | 1,50 | 58 | 100 | | 208 | 2,50 | |
| | 1-501.6 | 1,50 | 80 | 120 | | 250 | 3,00 | |
| | 1-501.7 | 1,50 | 60 | 140 | | 250 | 3,00 | |
| | 1-501.8 | 1,50 | 40 | 160 | | 250 | 3,00 | |
| | U - PROFIL (distanční) | | | | | | | Z X |
| | 1-502.1 | 1,50 | 130 | 60 | | 250 | 3,00 | |
| | 1-502.2 | 1,50 | 120 | 70 | | 250 | 3,00 | |
| | 1-502.3 | 1,50 | 110 | 80 | | 250 | 3,00 | |
| | 1-502.4 | 1,50 | 162 | 90 | | 312 | 3,74 | |
| | 1-502.5 | 1,50 | 152 | 100 | | 312 | 3,74 | |
| | 1-502.6 | 1,50 | 132 | 120 | | 312 | 3,74 | |
| | 1-502.7 | 1,50 | 112 | 140 | | 312 | 3,74 | |
| | 1-502.8 | 1,50 | 196 | 160 | | 416 | 4,99 | |
| | Ω - PROFIL (distanční) | | | | | | | Z X |
| | 1-503.1 | 1,50 | 90 | 80 | 47 | 416 | 4,99 | |
| | 1-503.2 | 1,50 | 67 | 100 | 58 | 416 | 4,99 | |
| | 1-503.3 | 1,50 | 44 | 120 | 70 | 416 | 4,99 | |
| | 1-503.4 | 1,50 | 136,5 | 130 | 76 | 625 | 7,50 | |
| | 1-503.5 | 1,50 | 125,5 | 140 | 81 | 625 | 7,50 | |
| | 1-503.6 | 1,50 | 102,5 | 160 | 93 | 625 | 7,50 | |
| | 1-503.7 | 1,50 | 79,5 | 180 | 104 | 625 | 7,50 | |
| <p>KONZOLA DISTANČNÍHO REKTIFIKOVATELNÉHO J PROFILU</p> | J - PROFIL (distanční rektifikovatelný) | | | | | | | Z X |
| | 1-504.1 | 1,50 | 50 | 60 | | 125 | 1,50 | |
| | 1-504.2 | 1,50 | 61 | 80 | | 156 | 1,87 | |
| | 1-504.3 | 1,50 | 63 | 100 | | 178 | 2,14 | |
| | 1-504.4 | 1,50 | 63 | 130 | | 208 | 2,50 | |
| | 1-504.5 | 1,50 | 65 | 170 | | 250 | 3,00 | |
| <p>OVÁLNÝ OTVOR Ø10,5 DÉLKA 30 mm</p> | KONZOLA (distančního rektifik. J profilu) | | | | | | | Z X |
| | 1-805.1 | 3,00 | 60 | | | 110 | 0,16/ks | |
| | 1-805.2 | 3,00 | 80 | | | 130 | 0,19/ks | |
| | 1-805.3 | 3,00 | 100 | | | 150 | 0,22/ks | |
| | 1-805.4 | 3,00 | 120 | | | 170 | 0,24/ks | |
| | 1-805.5 | 3,00 | 140 | | | 190 | 0,27/ks | |
| | 1-805.6 | 3,00 | 160 | | | 210 | 0,30/ks | |
| | VÝZTUŽNÝ ÚHELNIK | | | | | | | X |
| | 2-313.1 | 1,00 | 85 | 415 | | 500 | 4,00 | |
| | 2-313.2 | 1,00 | 130 | 495 | | 625 | 5,00 | |
| | DRŽÁK ATIKY | | | | | | | X |
| | 2-410.1 | 1,25 | 85 | | | 125 | 1,25 | |
| | 2-410.2 | 1,25 | 510 | | | 250 | 2,50 | |
| | DRŽÁK LEMOVACÍHO PROFILU | | | | | | | Z X |
| | 2-511.1 | 1,50 | 150 | 122 | | 312 | 3,74 | |
| | 2-511.2 | 1,50 | 220 | 156 | | 416 | 4,99 | |
| | OKRAJOVÁ VÝZTUHA | | | | | | | Z X |
| | 2-512.1 | 1,50 | 182 | 110 | | 312 | 3,74 | |